

Installation/Care instructions

NOTE: Our warranty does not cover improperly installed product or exposure to unauthorized chemicals.

* All kit materials and tires must be dry and kept in a climate no colder than **65 deg F** for a min of **1 hr** before installation.

- Clean tire sidewall with a strong detergent, (no petroleum, citrus) and rub dry. Up to 5 applications of cleaner and scrubbing are reqd. **(Especially for new tires, they are full of harmful acids that will cause staining if not stripped clean)** Next, scuff the surface w the supplied sand paper.
- **NOTE: Do not remove rubber with the sand paper.** Only a light scuff is needed. Removing material from the sidewall could compromise tire integrity.

Wipe the sidewall **AND THE LETTERS** with 50% - 70%

- Isopropyl alcohol, (dillute w water if concentration is higer.)
Racing font™ tips below- instructions cont. on reverse side.

Racing Font™ Installation Tips

When placing the Racing Font™ Letters there are some things to note. One of the keys to the superior look of our letters is that they are **INDIVIDUALLY CURVED**. This allows them to nest together tightly around the curved sidewall. This also requires special attention to assure the letters are not placed upside down.

Letters to watch out for are H, I, N, O, and S.

Placing these upside down will result in an unsatisfactory appearance. The curve will be opposite of the desired direction



